


# Product data sheet

Specifications



## standard auxiliary contact for fixed Compact NS630b to Compact NS3200, SD contact

33004

### Main

Product Or Component Type	Auxiliary contact
Device Short Name	SD
Device Application	Breaker status monitoring
Range Compatibility	ComPact ComPact NS630b...1600 ComPact ComPact NS1600b...3200
Signal Contacts Composition	1 NO/NC

### Complementary

Local Signalling	Trip indicator for relay trip indicator
Auxiliary Contacts Type	Standard
Mounting Mode	Clip-on
[Ith] Conventional Free Air Thermal Current	6 A
Minimum Load	100 mA at 24 V DC

### Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	2.0 cm
Package 1 Width	4.0 cm
Package 1 Length	5.0 cm
Package 1 Weight	800.0 g

### Contractual warranty

Warranty	18 months
----------	-----------

List Price displayed is VAT EXCLUSIVE.

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

## Well-being performance

✓	Reach Free Of Svhc	
✓	Toxic Heavy Metal Free	
✓	Mercury Free	
✓	Rohs Exemption Information	Yes
✓	Pvc Free	
Reach Regulation	REACH Declaration	
Eu Rohs Directive	Compliant EU RoHS Declaration	
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)	
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	