# Product data sheet

Specifications





# impulse relay iTLI - 2P - 1NO+1NC - 16A - coil 12 VAC 50/60Hz- 6 VDC

A9C30015

#### Main

Acti9
Acti9 iTL
Impulse relay
iTLi
Changeover relay
2P
1 NO + 1 NC
16 A
AC
12 V AC 50/60 Hz 6 V DC

## Complementary

Network Frequency	50/60 Hz
[Ue] Rated Operational Voltage	250 V AC 50/60 Hz
Control Type	Coil deconnection
	Remote and manual control
Control Signal Type	Impulse
Switching Frequency	100 switching operations/day
	5 switching operations/minute
Impulse Duration	50 ms1 s
Remote Control Type	Illuminated push-button 3 mA
Local Signalling	ON/OFF indication
Mounting Mode	Fixed
Mounting Support	DIN rail
9 Mm Pitches	2
Height	84 mm
Width	18 mm
Depth	60 mm
Electrical Durability	AC-21: 200000 cycles
	AC-22: 100000 cycles

List Price displayed is VAT EXCLUSIVE.

Connections - Terminals	Control circuit: tunnel type terminals 1 cable(s) 0.54 mm <sup>2</sup> rigid	
	Control circuit: tunnel type terminals 1 cable(s) 0.54 mm <sup>2</sup> rigid with cable end	
	Control circuit: tunnel type terminals 1 cable(s) 14 mm <sup>2</sup> flexible	
	Control circuit: tunnel type terminals 1 cable(s) 14 mm <sup>2</sup> flexible with ferrule	
	Power circuit: tunnel type terminals 1 cable(s) 1.54 mm <sup>2</sup> rigid Power circuit: tunnel type terminals 1 cable(s) 1.54 mm <sup>2</sup> rigid with cable end Power circuit: tunnel type terminals 1 cable(s) 1.54 mm <sup>2</sup> flexible	
		Power circuit: tunnel type terminals 1 cable(s) 1.54 mm <sup>2</sup> flexible with ferrule
		Wire Stripping Length
	Tightening Torque	1 N.m
Range Compatibility	Acti 9 iATLm	
	Acti 9 iATLs	
	Acti 9 iETL iTL 16	

## Environment

Standards	EN 669-2-2 EN 669-1
Product Certifications	CCC GOST
Quality Labels	CEBEC VDE NF IMQ KEMA
Noise Level	60 dB
Ip Degree Of Protection	IP20 conforming to IEC 60529 (on opening) IP40 conforming to IEC 60529 (in enclosure)
Pollution Degree	3
Tropicalisation	2
Relative Humidity	95 % at 55 °C
Ambient Air Temperature For Operation	-2050 °C
Ambient Air Temperature For Storage	-4070 °C

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	1.8 cm
Package 1 Width	7.0 cm
Package 1 Length	8.5 cm
Package 1 Weight	113.0 g
Unit Type Of Package 2	BB1
Number Of Units In Package 2	12
Package 2 Height	8.0 cm
Package 2 Width	9.0 cm
Package 2 Length	22.5 cm
Package 2 Weight	1.412 kg
Unit Type Of Package 3	\$03
Number Of Units In Package 3	144
Package 3 Height	30.0 cm

Package 3 Width	30.0 cm
Package 3 Length	40.0 cm
Package 3 Weight	17.46 kg

# **Contractual warranty**

Warranty

18 months

# Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

#### Well-being performance

Mercury Free
Rohs Exemption Information Yes
Halogen Free Plastic Parts Product

### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations