Product data sheet

Specifications





Acti9 iPB 1NO single push button grey - indicator light green 12-48Vac/dc

A9E18038

() Discontinued on: Aug 29, 2023

Main

| Range Of Product | Acti9 |
|---------------------------|------------------------------|
| Product Name | Acti9 iPB |
| Product Or Component Type | Push-button |
| Device Short Name | iPB |
| Standards | IEC 60669-1 IEC 60947-5-1 |

Complementary

| Contacts Type And Composition | 1 NO |
|---|---|
| [le] Rated Operational Current | 20 A |
| [Ue] Rated Operational Voltage | 250 V AC |
| Control Type | 1 push-button grey |
| Local Signalling | LED indicator green, service life 100000 h of constant lighting efficiency (consumption 0.3 W) |
| Signalling Circuit Voltage | AC: 1248 V 50/60 Hz DC: 1248 V |
| Mounting Mode | Fixed |
| Mounting Support | 35 mm symmetrical DIN rail |
| Comb Busbar And Distribution Block Compatibility | Upside: Clario Upside: Librio Upside: ProDis |
| 9 Mm Pitches | 2 |
| Height | 82 mm |
| Width | 18 mm |
| Depth | 71.5 mm |
| Colour | White |
| Electrical Durability | AC-22: 30000 cycles AC 50/60 Hz |
| Connections - Terminals | Staggered tunnel terminal1 cable(s) 0.5 mm ² rigid Staggered tunnel terminal1 cable(s) 0.5 mm ² flexible Staggered tunnel terminal1 cable(s) 0.5 mm ² flexible with ferrule Staggered tunnel terminal2 cable(s) 2.5 mm ² rigid Staggered tunnel terminal2 cable(s) 2.5 mm ² flexible Staggered tunnel terminal2 cable(s) 2.5 mm ² flexible |
| Wire Stripping Length | 9 mm |
| Tightening Torque | 1 N.m |

List Price displayed is VAT EXCLUSIVE.

Environment

| Tropicalisation | 2 |
|--|---------------|
| Relative Humidity | 95 % at 55 °C |
| Ambient Air Temperature For Operation | -3570 °C |
| Ambient Air Temperature For Storage | -4080 °C |

Packing Units

| • | |
|------------------------------|----------|
| Unit Type Of Package 1 | PCE |
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 6.6 cm |
| Package 1 Width | 1.8 cm |
| Package 1 Length | 8.2 cm |
| Package 1 Weight | 46 g |
| Unit Type Of Package 2 | BB1 |
| Number Of Units In Package 2 | 12 |
| Package 2 Height | 7.8 cm |
| Package 2 Width | 9.8 cm |
| Package 2 Length | 23.3 cm |
| Package 2 Weight | 605 g |
| Unit Type Of Package 3 | S03 |
| Number Of Units In Package 3 | 108 |
| Package 3 Height | 30 cm |
| Package 3 Width | 30 cm |
| Package 3 Length | 40 cm |
| Package 3 Weight | 5.942 kg |
| | |

Contractual warranty

Warranty

18 months

Sustainability Screen

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Mercury Free

Rohs Exemption Information Yes

Halogen Free Plastic Parts & Cables Product

Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|---|
| Eu Rohs Directive | Compliant with Exemptions |
| China Rohs Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile | No need of specific recycling operations |