# Product data sheet

Specifications





# single contact block with body/ fixing collar 2NO plug-in connector

ZB4BZ1034

() Discontinued on: Nov 1, 2020

#### () Discontinued

#### Main

| Range Of Product              | Harmony XB4                    |
|-------------------------------|--------------------------------|
| Product Or Component Type     | Complete body/contact assembly |
| Device Short Name             | ZB4                            |
| Fixing Collar Material        | Zamak                          |
| Sale Per Indivisible Quantity | 1                              |
| Head Type                     | Standard                       |
| Contacts Type And Composition | 2 NO                           |
| Contact Operation             | Slow-break                     |
| Contact Block Type            | Single                         |
| Device Composition            | Body<br>Fixing collar          |
| Connections - Terminals       | Plug-in connector              |

#### Complementary

| Cad Overall Width                              | 30 mm  |
|--|--|
| Cad Overall Height                             | 47 mm  |
| Cad Overall Depth                              | 37 mm  |
| Terminals Description Iso N°1                  | (13-14)NO  |
| Net Weight                                     | 0.058 kg   |
| Contacts Usage                                 | Standard contacts  |
| Positive Opening                               | Without  |
| Operating Travel                               | 2.6 mm (NO changing electrical state)<br>4.3 mm (total travel) |
| Operating Torque                               | 0.05 N.m NO changing electrical state                          |
| Mechanical Durability                          | 5000000 cycles   |
| Contacts Material                              | Silver alloy (Ag/Ni)   |
| Short-Circuit Protection                       | 4 A cartridge fuse type gG conforming to EN/IEC 60947-5-1      |
| [Ith] Conventional Free Air<br>Thermal Current | 10 A conforming to EN/IEC 60947-5-1                            |
| [Ui] Rated Insulation Voltage                  | 250 V (pollution degree 3) conforming to EN 60947-1            |
| [Uimp] Rated Impulse Withstand                 | 4 kV conforming to EN 60947-1                                  |

Voltage

List Price displayed is VAT EXCLUSIVE.

| [le] Rated Operational Current | 3 A at 240 V, AC-15, A300 conforming to EN/IEC 60947-5-1<br>6 A at 120 V, AC-15, A300 conforming to EN/IEC 60947-5-1<br>0.1 A at 250 V, DC-13, R300 conforming to EN/IEC 60947-5-1<br>0.22 A at 125 V, DC-13, R300 conforming to EN/IEC 60947-5-1  |
|--------------------------------|--|
| Electrical Durability          | 10000000 cycles, AC-15, 1 A at 230 V, operating rate <3600 cyc/h, load factor: 0.5<br>conforming to EN/IEC 60947-5-1 appendix C<br>10000000 cycles, AC-15, 1.5 A at 120 V, operating rate <3600 cyc/h, load factor: 0.5<br>conforming to EN/IEC 60947-5-1 appendix C<br>10000000 cycles, AC-15, 3 A at 24 V, operating rate <3600 cyc/h, load factor: 0.5<br>conforming to EN/IEC 60947-5-1 appendix C<br>10000000 cycles, DC-13, 0.15 A at 110 V, operating rate <3600 cyc/h, load factor:<br>0.5 conforming to EN/IEC 60947-5-1 appendix C<br>10000000 cycles, DC-13, 0.4 A at 24 V, operating rate <3600 cyc/h, load factor: 0.5<br>conforming to EN/IEC 60947-5-1 appendix C |
| Electrical Reliability         | $\Lambda$ < 10exp(-6) at 5 V, 1 mA in clean environment conforming to EN/IEC 60947-5-4 $\Lambda$ < 10exp(-8) at 17 V, 5 mA in clean environment conforming to EN/IEC 60947-5-4   |

#### Environment

| Protective Treatment                     | ТН   |
|--|--|
| Ambient Air Temperature For<br>Storage   | -4070 °C   |
| Ambient Air Temperature For<br>Operation | -4070 °C   |
| Ip Degree Of Protection                  | IP20 conforming to IEC 60529   |
| Standards                                | UL 508<br>EN/IEC 60947-5-4<br>EN/IEC 60947-5-1<br>CSA C22.2 No 14<br>EN/IEC 60947-5-5<br>EN/IEC 60947-1<br>JIS C8201-5-1<br>JIS C8201-1  |
| Product Certifications                   | CSA<br>BV<br>UL<br>GL<br>LROS (Lloyds register of shipping)<br>DNV   |
| Vibration Resistance                     | 5 gn (f= 2500 Hz) conforming to IEC 60068-2-6  |
| Shock Resistance                         | 30 gn (duration = 18 ms) for half sine wave acceleration conforming to IEC 60068-2-27<br>50 gn (duration = 11 ms) for half sine wave acceleration conforming to IEC 60068-2-27 |

### **Packing Units**

| Unit Type Of Package 1       | PCE    |
|------------------------------|--------|
| Number Of Units In Package 1 | 1      |
| Package 1 Height             | 3.4 cm |
| Package 1 Width              | 4.5 cm |
| Package 1 Length             | 5.4 cm |
| Package 1 Weight             | 59 g   |

# **Contractual warranty**

Warranty

18 months

## Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

### Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes


#### **Certifications & Standards**

| Reach Regulation         | REACh Declaration   |
|--------------------------|---|
| Eu Rohs Directive        | Pro-active compliance (Product out of EU RoHS legal scope)<br>EU RoHS Declaration   |
| China Rohs Regulation    | China RoHS declaration  |
| Environmental Disclosure | Product Environmental Profile   |
| Weee                     | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile      | End of Life Information   |

# Product data sheet

#### **Dimensions Drawings**

#### Dimensions



4

### Product data sheet ZB4BZ1034

Mounting and Clearance

Panel Cut-out for Pushbuttons, Switches and Pilot Lights (Finished Holes, Ready for Installation)

